

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 718 042 B1**

(12)

## EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention  
of the grant of the patent:  
05.02.2003 Bulletin 2003/06

(21) Application number: 95308064.5

(22) Date of filing: 10.11.1995

(51) Int Cl.7: **B05B 7/08**, B05B 7/06,  
B05B 7/12, B05B 7/24,  
B29B 7/24, B29B 7/74,  
B29C 41/36, B05B 7/14,  
B05B 5/03

(54) **Two component external mix spray gun**

Zweikomponentenspritzpistole mit externer Mischung

Pistolet-pulvérisateur à deux composants à mélange après décharge

(84) Designated Contracting States:  
AT BE CH DE ES FR GB IE IT LI PT SE

(30) Priority: 08.12.1994 US 351932

(43) Date of publication of application:  
26.06.1996 Bulletin 1996/26

(73) Proprietor: **RANSBURG CORPORATION**  
Indianapolis, Indiana 46208-0511 (US)

(72) Inventor: **Fritz, Alan H.**  
Toledo, Ohio 43611 (US)

(74) Representative: **Townsend, Victoria Jayne et al**  
Fry Heath & Spence LLP  
The Gables  
Massetts Road  
Horley, Surrey RH6 7DQ (GB)

(56) References cited:

EP-A- 0 063 707	EP-A- 0 254 564
GB-A- 863 712	US-A- 3 507 451
US-A- 4 175 702	US-A- 4 426 039
US-A- 4 854 504	US-A- 4 928 884
US-A- 5 303 865	

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

**EP 0 718 042 B1**

## Description

[0001] This invention relates to spray guns and more particularly to an improved spray gun for applying two component materials in which a catalyst or activator is added to a primary material such as an adhesive or a paint according to the prior art portions of claim 1 or 9. A spray gun comprising these features is known from EP 254 564.

[0002] In the past, sprayable paints and adhesives frequently have been organic solvent based. The solvent is used to maintain the material in a sufficiently fluid state to permit spraying. Organic solvents were selected to achieve rapid drying. As the sprayed material dries, solvent enters the atmosphere and can be hazardous. Recently, there has been an increasing demand for two component materials in which a water borne coating or adhesive material is chemically hardened or activated through the use of a separate catalyst or activator. As used hereinafter, the term "catalyst" will be used generically to describe any catalyst or activator or other type of chemical which is added to a coating material to promote a change in the material. Some types of adhesive and other types of coating materials, such as epoxy type materials, may have a relatively long pot life after mixing with a catalyst. The long pot life permits mixing the components either prior to delivery to a spray gun or internally in the spray gun. The pot life of the mixture is sufficiently long as to permit cleaning of the spray gun after spraying. Other types of two component materials must be mixed externally to the spray gun, since there is not a sufficient pot life of the mixture to permit easy cleaning of the spray gun after the material is mixed or contacted with the catalyst.

[0003] In prior art spray guns for externally mixed two component materials, the coating or adhesive material is sprayed from a modified conventional spray gun. The spray gun has been modified by mounting a mechanically operated catalyst valve on the gun. The catalyst valve has been mounted towards the rear of the spray gun body where it is easily connected through linkages to be operated by the existing spray gun trigger. The linkages are adjusted to open the catalyst valve immediately prior to opening the fluid valve for the coating or adhesive material. This assures that all sprayed material will be exposed to the catalyst. In one prior art spray gun, the catalyst valve was connected through a small tube to spray the catalyst at the atomized fluid at a point downstream from an air cap. In this arrangement, the catalyst was sprayed only at one side of the atomized fluid envelope. Consequently, the atomized fluid was not uniformly exposed to the catalyst. The material spaced furthest from the catalyst nozzle was not necessarily exposed to sufficient catalyst, resulting in a defective application of paint or adhesive. In an improved prior art spray gun, the catalyst was injected into a pattern shaping air chamber in the air cap or upstream from the air cap for mixing with the pattern shaping air. This arrangement

provides superior contact between the catalyst and the atomized material immediately downstream from the spray gun nozzle. However, there have still been some problems with this arrangement. Because the valve has been located at or near the rear end of the gun body in order to connect the operating linkages to the trigger, a relatively long tube is used to deliver the catalyst from the valve to the pattern shaping air chambers. When the gun is shut off and set down, catalyst in the tube sometimes has drained into the pattern shaping air chamber. This can result in a burst of catalyst in the pattern shaping air when the spray gun is first triggered. Also, the linkages connecting the catalyst valve to the trigger have been prone to damage and misadjustment which can result in an improper timing of the opening of the catalyst valve relative to the opening of the main fluid valve.

[0004] According to one aspect of the invention there is provided a two component external mix spray gun according to claim 1.

[0005] According to a second aspect of the invention there is provided a spray gun for atomizing a fluid and contacting the atomized fluid with a catalyst at a location external to the spray gun according to independent claim 9.

[0006] According to a third aspect of the invention there is provided a method for spraying a material having first and second components, comprising the steps of (a) turning on a flow of pressurized air to a nozzle assembly, at least a portion of such flow of air shaping the pattern of atomized first material, (b) opening a second material valve in response to the flow of pressurized air to the nozzle assembly to inject second material into the flow of pattern shaping air; (c) opening a first material valve after the flow of pressurized pattern shaping air is turned on to deliver first material to the nozzle assembly for atomization; and (d) contacting the atomized first material with the flow of pattern shaping and second material.

[0007] Since the catalyst will be injected into a chamber containing pressurized pattern shaping air, the catalyst must have a pressure greater than the air pressure in order to flow into the pattern shaping air chamber. Typically, the catalyst will be located in a pressurized container placed on the floor near the location where the fluid is sprayed. The pressure in the catalyst container must not only be sufficient to overcome the air pressure, but it also must overcome the pressure head created by the maximum height of the spray gun above the container. Since the pressure head may vary during spraying, it is preferable to use a higher catalyst pressure than the minimum required pressure to eliminate pressure head variations. A metering orifice then is placed in the catalyst line near but upstream from the catalyst valve to control the rate that the catalyst is injected into the pattern shaping air.

[0008] Accordingly, it is an aim of the present invention to provide an improved external mix two component

spray gun.

[0009] An embodiment of the invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

Figure 1 is a side elevational view of a two component external mix spray gun according to the invention;

Figure 2 is an enlarged vertical cross sectional view through the front end of the spray gun body and the nozzle assembly for atomizing fluid;

Figure 3 is a cross sectional view as taken along line 3-3 of Figure 2;

Figure 4 is a cross sectional view as taken along line 4-4 of Figure 2;

Figure 5 is an enlarged fragmentary cross sectional view of the baffle as taken along line 5-5 of Figure 4; and

Figure 6 is a bottom view of the baffle of Figure 5.

[0010] Referring to Figure 1 of the drawings, a spray gun 10 is illustrated according to a preferred embodiment of the invention. The illustrated spray gun 10 is a hand held HVLP spray gun which uses a high volume low pressure flow of atomization and pattern shaping air at a nozzle assembly 11 for atomizing a primary component of a two component material, such as a water borne adhesive, and for spraying such material in a flattened or fan shaped pattern. The invention is illustrated as a modification to the spray gun shown in United States Patent 5,209,405. However, it will be appreciated that the invention is equally applicable to a spray gun which uses high pressure air for atomization and pattern shaping and to an automatic spray gun which, for example, is mounted on a fixed stand or on a reciprocator or on an industrial robot for industrial applications. In an automatic spray gun, the trigger operated air and fluid valves are replaced with valves operated by a programmable controller.

[0011] The spray gun 10 includes a body 12 having a handle 13, a central portion 14 and a barrel end 15. The nozzle assembly 11 is secured to the barrel end 15. High pressure air from a suitable compressor or shop air line (not shown) is supplied to the gun 10 through a hose 16 which connects to a fitting 17 on a free end 18 of the gun handle 13. Air flows from the fitting 17 through a passage 19 in the handle 13 to a normally closed valve 20. A manifold block 21 also is attached to the handle end 18. A fluid hose 22 and a catalyst hose 23 are connected to the manifold block 21. The three hoses 16, 22 and 23 are all supported from the gun handle end 18 so as to minimize their effect on the balance of the gun 10 during operation. If desired, the hoses 16, 22 and 23 may be connected together, for example, by clips or plastic ties, to help manage the hoses during operation of the spray gun 10. The manifold block 21 has a first internal passage (not shown) which connects the fluid hose 22 to a fluid hose 24 which leads to a fitting 25 on

the barrel end 15 of the gun body 12. A second internal passage (not shown) in the manifold 21 connects the catalyst hose 23 to a catalyst hose 26 which is connected to a pilot valve 27. As will be described in greater detail below, when the valve 27 is opened, catalyst is injected into pattern shaping air which impinges on the mixes with the atomized fluid.

[0012] A screw 29 secures a trigger 28 to the central portion 14 of the body 12 for pivoting towards and away from the handle 13. As the trigger 28 is squeezed to turn on the spray gun 10, a plunger 30 is moved to open the air valve 20, allowing the compressed air in the passage 19 to flow into a passage 31 which connects to the nozzle assembly 11. The air flow in the passage 31 is divided into two portions: a flow of atomization air for atomizing the fluid from the hose 24 and a flow of pattern shaping air which flattens the envelope of the atomized fluid into a fan shaped pattern. The pressures of the atomization air and of the pattern shaping air are reduced to desired low levels before the air is discharged from the nozzle assembly 11. A knob 32 operates a valve needle 33 to control the flow of pattern shaping air to produce a desired spray pattern. As the trigger 28 is further squeezed after the valve 20 is opened, a valve needle 34 is moved to open a fluid valve 35 (Figure 2) in the nozzle assembly 11. A knob 36 is provided for adjusting the amount of fluid which will be discharged when the fluid valve 35 is fully opened by limiting the axial travel of the valve needle 34.

[0013] The pilot valve 27 is normally closed, inhibiting the flow of catalyst to the nozzle assembly 11. When sufficient air pressure is applied to a control port 37, the valve 27 is opened and catalyst flows into a passage 38 (Figure 3) in the barrel end 15. A fitting 39 is secured to the handle 13 to connect a hose 40 to the passage 31. An opposite end of the hose 40 is connected to the catalyst valve control port 37. Thus, when the trigger 28 is initially squeezed to open the valve 20 and pressurized air flows into the passage 31, the pressurized air will be applied to the control port 37 to open the catalyst valve 27 and catalyst will be injected into the flowing pattern shaping air. It will be appreciated that the pattern shaping air will be under at least a low pressure as it flows in the spray gun 10. In order to assure that the catalyst is injected into the pattern shaping air, the catalyst in the hose 23 is maintained at a pressure greater than the pattern shaping air pressure at the point of injection plus the maximum pressure head resulting from locating the spray gun 10 above the pressurized catalyst source. A calibrated orifice 41 is placed in the catalyst hose 26 near the valve 27 to limit the flow when the valve 27 is opened. A plastic sleeve or tube 42 may be placed over the hoses 24 and 26 and the orifice 41 for protection and to keep the hoses 24 and 26 together. Alternately, the orifice 41 may be replaced with an in-line flowmeter with an integral needle valve for in-process flow measurement and control.

[0014] Internal details of the spray gun 10 and partic-

ularity of the nozzle assembly 11 are shown in Figures 2-6. The nozzle assembly 11 includes a fluid tip 48, a baffle 49, an air cap 50 and a retaining ring 51. A sleeve 52 is mounted in and projects from a passage 53 in the gun barrel end 15. The sleeve 52 has an internally threaded central opening 54. The fluid tip 58 has a threaded end 55 which engages the threaded sleeve opening 54. The baffle 49 is secured to the spray gun body 12 by clamping between a radial flange 56 on the fluid tip 58 and a front face 57 on the barrel end 15. An annular gasket 58 provides a fluid tight seal between the gun body 12 and the baffle 48. The baffle 48 has a threaded perimeter 59. The retaining ring 51 is threaded onto the baffle 49 to retain the air cap 50 on the spray gun 10.

[0015] The fluid to be atomized which is supplied to the barrel end 15 through the hose 24 passes into the opening 54 in the sleeve 52. The fluid valve needle 34 passes coaxially through the opening 54 and an axial chamber 60 in the fluid tip 48 to a tapered end 61 which seals against the fluid tip 48 to form the valve 35. When the trigger 28 is squeezed sufficiently, the valve needle 34 is moved in an axial direction to open the valve 35 and fluid is discharged through the annular orifice formed between the tapered valve needle end 61 and the fluid tip chamber 60.

[0016] As best illustrated in Figures 2 and 4, an annular groove 62 is formed in the barrel face 57. The passage 31 (Figure 1) in the spray gun body 14 is split into separate high pressure air passages for atomization air and pattern shaping air. High pressure atomization air flows from the passage 31 through two openings 63 and 64 into the groove 62. A short tube 65 is pressed or otherwise secured to project from an opening 66 in the baffle. When the baffle 49 is mounted on the gun body 12, the tube 65 extends into an opening 66' in the gun body 12 for receiving pattern shaping air. The tube 65 has a calibrated internal orifice 67 for lowering the pressure of the pattern shaping air to a desired low level. In addition, the valve needle 33 may be adjusted to further limit the flow of pattern shaping air. From the orifice 67, the pattern shaping air flows into an annular chamber 68 in the baffle 49.

[0017] From the annular groove 62, the atomization air flows through one or more calibrated small diameter pressure dropping passages 69 to an annular chamber 70 formed between the baffle 49 and the fluid tip 48. The air pressure drops as the air flows through the passages 69 to a desired low level. As the air pressure drops, its volume expands to provide the high volume low pressure air flow needed for fluid atomization. From the chamber 70, the atomization air flows through a plurality of circumferentially spaced distribution openings 71 in the fluid tip flange 56 to a chamber 72 formed between the air cap 50 and the fluid tip 48. Atomization air is discharged from an annular orifice 73 formed between an end 74 of the fluid tip 48 and the air cap 50. The discharged atomization air surrounds and atomizes the flu-

id as it is discharged from the orifice 61.

[0018] As shown in Figures 3 and 5, a short tube 75 projects from the front face 57 on the spray gun barrel end 15. The catalyst passage 38 extends through the tube 75. When the baffle 49 is positioned against the barrel face 57, the tube 75 extends into a baffle opening 76 and is sealed by an O-ring 77. A passage 78 in the baffle 49 connects the catalyst passage 38 with the pattern shaping air chamber 68. The chamber is closed around its perimeter by a tubular sleeve 79 which is pressed onto and forms a part of the baffle 49. As shown in Figures 2 and 6, two notches 80 are formed in the sleeve 79 to connect the baffle chamber 68 with a chamber 81 formed between the fluid tip 48, the baffle 49, the air cap 50 and the retaining ring 51. The notches 80 are preferably located at the top and bottom of the baffle 49 and are circumferentially spaced 90° from the catalyst passage 78. This provides a tortuous flow path for the mixed catalyst and pattern shaping air, allowing the catalyst time to thoroughly mix with the pattern shaping air. Pattern shaping air passages 82 in the air cap 50 receive the pattern shaping air with the catalyst droplets from the chamber 81. The air cap 50 has two horns 83 which are spaced on diametrically opposite sides of the fluid tip end 74. The passages 82 direct the pattern shaping air/catalyst at opposite sides of the envelope of atomized fluid for flattening the envelope into a fan shaped pattern and also for contacting the atomized fluid with the catalyst externally to the spray gun 10. The air cap 50 may be rotated to provide a desired orientation to the flattened pattern. For the sake of illustration, the horns 83 are shown in a vertical arrangement, which results in a horizontal pattern. Most frequently, the horns 83 are located in a plane horizontal to the spray gun 10 to produce a vertical pattern.

[0019] The spray gun 10 is particularly useful for applying a two component water borne adhesive such as Bondmaster adhesive sold by National Starch & Chemical Company of Bridgewater, New Jersey. This adhesive is a polychloroprene which is activated by citric acid. Although it is important that the atomized adhesive come into contact with the activator, the mix ratio is not as critical as with some two component materials. When a higher degree of control over the catalyst to fluid mix ratio is desired, flow meters may be placed in the catalyst and fluid supply lines and orifice 41 is eliminated from the catalyst line 26.

[0020] It will be appreciated that various modifications and changes may be made to the above described preferred embodiment of a two component external mix spray gun without departing from the scope of the following claims. For example, as indicated above, the invention is equally applicable to a hand held spray gun as described and shown or to an automatic spray gun where the manual trigger is replaced with air and fluid valves which are operated by a controller. Although the catalyst valve 27 is illustrated as a valve secured to the side of a conventional spray gun, it will be appreciated

that the catalyst valve may be formed as an integral part of the spray gun inside the gun body 12.

#### Claims

1. A two component external mix spray gun (10) having a nozzle assembly (11), an air valve (20) for controlling the flow of pattern shaping air to the nozzle assembly (11), a fluid valve (35) for controlling the flow of fluid to the nozzle assembly (11), and catalyst injection means responsive to the opening of the air valve (20) for injecting catalyst into the flowing pattern shaping air in the spray gun (10), the catalyst injection means comprising a pneumatically operated catalyst valve (27), the catalyst valve (27) having an inlet port connected to a pressurized catalyst hose (23), an outlet port connected to a pattern shaping air passage (38) in the spray gun and a pilot air port (37) connected to receive pressurized air from the air valve (20) when the air valve (20) is opened, the catalyst valve (27) opening in response to pressurized air at the pilot air port (37), **characterised by** means for opening the air valve (20) prior to opening the fluid valve (35) when the spray gun (10) is turned on and for closing the fluid valve (35) prior to the air valve (20) when the spray gun (10) is turned off and by the catalyst valve being mounted on the spray gun (10).
2. A two component external spray mix gun as claimed in claim 1 wherein the means for opening the air valve (20) prior to opening the fluid valve (35) when the spray gun is turned on and for closing the fluid valve (35) prior to the air valve when the gun is turned off comprises a trigger (28) configured to cause sequential opening and closing of the air valve (20) and fluid valve (35).
3. A two component external mix spray gun as claimed in claim 1 or 2, **characterised in that** the catalyst valve (27) is mounted on the spray gun (10) adjacent the nozzle assembly (11).
4. A two component external mix spray gun (10) as claimed in claim 3, and further including orifice means for limiting the flow of catalyst to the nozzle assembly (11) when the catalyst valve (27) is opened.
5. A two component external mix spray gun (10) as claimed in claim 3, **characterised in that** the spray gun is a hand held spray gun (10) having the nozzle assembly (11) secured to one end of a body (12), the body including a handle (13) having a free end, means for securing an air hose (22) to the handle end, a manifold (21) secured to said handle end, the manifold (21) having first and second passages, means securing a fluid hose to the manifold (21) to connect to the first passage, means securing a catalyst hose (23) to the manifold to connect to the second passage, a second fluid hose connecting from the first manifold passage to the body adjacent the nozzle assembly, and a second catalyst hose (26) connecting from the second manifold passage to the catalyst valve inlet port.
6. A two component external mix spray gun as claimed in claim 5, **characterised in that** orifice means are included in the second catalyst hose (26) for limiting the flow of catalyst to the nozzle assembly (11) when the catalyst valve (27) is opened.
7. A two component external mix spray gun as claimed in claim 6, **characterised in that** means are included for securing the second fluid hose (22) and the second catalyst hose (26) together.
8. A two component external mix spray gun as claimed in claim 1, **characterised in that** the air valve controls the flow of pattern shaping and atomization air.
9. A spray gun for atomizing a fluid and contacting the atomized fluid with a catalyst at a location external to the spray gun (10), the spray gun comprising a body (12), a nozzle assembly (11) secured to the body (12), an air valve adapted for controlling the flow of pattern shaping air to the nozzle assembly (11), a fluid valve adapted for controlling the flow of fluid to the nozzle assembly (11), a normally closed pneumatically operated catalyst valve (27) having a pressurized catalyst inlet port and an outlet port connected to a pattern shaping air passage (38) in the spray gun (10), the catalyst valve (27) opening to inject catalyst into a flow of pattern shaping air in the air passage (38) in response to an increase in air pressure downstream from the air valve (20) when the air valve (20) is opened, **characterised by** an air valve adapted for controlling the flow of atomization air to the nozzle assembly (11), triggering means for opening the air valve (20) prior to opening the fluid valve (35) when the spray gun (10) is turned on and for closing the fluid valve (35) prior to the air valve (20) when the spray gun is turned off, and by the catalyst valve (27) being mounted on the spray gun.
10. A method for spraying a material having first and second components **characterised in that** it comprises the steps of:
  - a) turning on a flow of pressurized air to a nozzle assembly (11), at least a portion of such flow of air shaping the pattern of atomized first material;

b) opening a second material valve in response to the flow of pressurised air to the nozzle assembly (11) to inject second material into the flow of pattern shaping air;

c) opening a first material valve after the flow of pressurized pattern shaping air is turned on to deliver first material to the nozzle assembly (11) for atomization; and

d) contacting the atomized first material with the flow of pattern shaping air and second material.

#### Patentansprüche

1. Zweikomponentensspritzpistole (10) mit externer Mischung, mit einer Düsenbaugruppe (11), einem Luftventil (20) zum Steuern des Musterformungs-  
luftstromes zur Düsenbaugruppe (11), einem Fluid-  
ventil (35) zum Steuern des Fluidstromes zur Dü-  
senbaugruppe (11), und Katalysator-Injektionsmit-  
tein, welche auf das Öffnen des Luftventils (20) an-  
sprechen, zur Injektion von Katalysator in die strö-  
mende Musterformungsluft in der Sprühpistole  
(10), wobei die Katalysatorinjektionsmittel ein  
pneumatisch betriebenes Katalysatorventil (27)  
enthalten, welches eine Einlassöffnung, welche mit  
einem unter Druck stehenden Katalysatorschlauch  
(23) verbunden ist, eine Auslassöffnung, welche mit  
einem Musterformungsluftdurchgang (38) in der  
Sprühpistole verbunden ist, und eine Pilotluftöff-  
nung (37) aufweist, welcher verbunden ist, um  
Druckluft vom Luftventil (20) zu erhalten, wenn das  
Luftventil (20) geöffnet wird, wobei das Katalysator-  
ventil (27) als Antwort auf die Druckluft an der Pi-  
lotluftöffnung (37) öffnet,  
**gekennzeichnet durch**  
Mittel zum Öffnen des Luftventils (20) vor dem Öff-  
nen des Fluidventils (35), wenn die Sprühpistole  
(10) eingeschaltet wird, und zum Schließen des  
Fluidventils (35) vor dem Luftventil (20), wenn die  
Sprühpistole (10) ausgeschaltet wird, und **durch**  
das Katalysatorventil, welches auf der Sprühpistole  
(10) montiert ist.
2. Zweikomponentensspritzpistole mit externer Mi-  
schung nach Anspruch 1, wobei die Mittel zum Öff-  
nen des Luftventils (20) vor dem Öffnen des Fluid-  
ventils (35), wenn die Sprühpistole eingeschaltet  
wird, und zum Schließen des Fluidventils (35) vor  
dem Luftventil, wenn die Pistole ausgeschaltet wird,  
einen Trigger (28) enthalten, welcher so konfiguriert  
ist, dass er das aufeinanderfolgende Öffnen und  
Schließen des Luftventils (20) und des Fluidventils  
(35) verursacht.

3. Zweikomponentensspritzpistole mit externer Mi-  
schung nach Anspruch 1 oder 2, **dadurch gekenn-  
zeichnet, dass** das Katalysatorventil (27) auf der  
Sprühpistole (10) benachbart zur Düsenbaugruppe  
(11) montiert ist.
4. Zweikomponentensspritzpistole (10) mit externer  
Mischung nach Anspruch 3, und ferner enthaltend  
Öffnungsmittel zum Begrenzen des Katalysator-  
stroms zur Düsenbaugruppe (11), wenn das Kata-  
lyikatorventil (27) geöffnet ist.
5. Zweikomponentensspritzpistole (10) mit externer  
Mischung nach Anspruch 3, **dadurch gekenn-  
zeichnet, dass** die Sprühpistole eine von Hand ge-  
haltene Sprühpistole (10) ist, welche die Düsenbau-  
gruppe (11) an einem Ende eines Körpers (12) be-  
festigt hat, wobei der Körper einen Griff (13) enthält,  
welcher ein freies Ende hat, Mittel zum Befestigen  
eines Luftschlauches (22) am Griffende, einen Ver-  
teiler (21), welcher an dem Griffende befestigt ist,  
wobei der Verteiler (21) erste und zweite Durchgän-  
ge hat, Mittel, welche einen Fluidschlauch am Ver-  
teiler (21) befestigen, um ihn mit dem ersten Durch-  
gang zu verbinden, Mittel, welche einen Katalysa-  
torschlauch (23) am Verteiler befestigen, um ihn mit  
dem zweiten Durchgang zu verbinden, einen zwei-  
ten Fluidschlauch, welcher den ersten Verteiler-  
durchgang mit dem Körper neben der Düsenbau-  
gruppe verbindet, und einen zweiten Katalysator-  
schlauch (26), welcher den zweiten Verteilerdurch-  
gang mit der Katalysatorventil-Einlassöffnung ver-  
bindet.
6. Zweikomponentensspritzpistole mit externer Mi-  
schung nach Anspruch 5, **dadurch gekennzeich-  
net, dass** Öffnungsmittel im zweiten Katalysator-  
schlauch (26) enthalten sind, um den Katalysator-  
strom zur Düsenbaugruppe (11) zu begrenzen,  
wenn das Katalysatorventil (27) geöffnet ist.
7. Zweikomponentensspritzpistole mit externer Mi-  
schung nach Anspruch 6, **dadurch gekennzeich-  
net, dass** Mittel enthalten sind, um den zweiten  
Fluidschlauch (22) und den zweiten Katalysator-  
schlauch (26) aneinander zu befestigen.
8. Zweikomponentensspritzpistole mit externer Mi-  
schung nach Anspruch 1, **dadurch gekennzeich-  
net, dass** das Luftventil den Strom der Musterfor-  
mungs- und Zerstäubungsluft steuert.
9. Spritzpistole zur Zerstäubung eines Fluids und  
Kontaktieren des zerstäubten Fluids mit einem Ka-  
talyikator an einer Stelle extern von der Spritzpistole  
(10), wobei die Sprühpistole enthält: einen Körper  
(12), eine Düsenbaugruppe (11), welche am Körper  
(12) befestigt ist, ein Luftventil, welches so ange-

passt ist, dass es den Musterformungsluftstrom zur Düsenbaugruppe (11) steuert, ein Fluidventil, welches so angepasst ist, dass es den Fluidstrom zur Düsenbaugruppe (11) steuert, ein normalerweise geschlossenes pneumatisch betriebenes Katalysatorventil (27), welches eine Einlassöffnung für unter Druck stehenden Katalysator und eine Auslassöffnung hat, welche mit einem Musterformungsluftdurchgang (38) in der Spritzpistole (10) verbunden ist, wobei das Katalysatorventil (27) öffnet, um Katalysator in einen Musterformungsluftstrom im Luftdurchgang (38) als Antwort auf eine Erhöhung des Luftdruckes stromabwärts des Luftventils (20) zu injizieren, wenn das Luftventil (20) geöffnet wird,

**gekennzeichnet durch**

ein Luftventil, welches so angepasst ist, dass es den Zerstäubungsluftstrom zur Düsenbaugruppe steuert, Triggermittel zum Öffnen des Luftventils (20) vor dem Öffnen des Fluidventils (35), wenn die Spritzpistole (10) eingeschaltet wird, und zum Schließen des Fluidventils (35) vor dem Luftventil (20), wenn die Spritzpistole ausgeschaltet wird, und durch das Katalysatorventil (27), welches auf der Sprühpistole montiert ist.

10. Verfahren zum Sprühen eines Materials, welches erste und zweite Komponenten aufweist, **dadurch gekennzeichnet, dass** es die Schritte enthält:

- a) Einschalten eines Druckluftstromes zu einer Düsenbaugruppe (11), wobei mindestens ein Teil solch eines Luftstromes das Muster des zerstäubten ersten Materials formt;
- b) Öffnen eines zweiten Materialventils als Antwort auf den Druckluftstrom zur Düsenbaugruppe (11), um ein zweites Material in den Musterformungsluftstrom zu injizieren;
- c) Öffnen eines ersten Materialventils, nachdem der unter Druck stehende Musterformungsluftstrom eingeschaltet wurde, um erstes Material zur Düsenbaugruppe (11) zur Zerstäubung zu liefern; und
- d) Kontaktieren des zerstäubten ersten Materials mit dem Musterformungsluftstrom und zweitem Material.

**Revendications**

1. Pistolet pulvérisateur à mélange externe de deux composants (10) comportant un agencement de buse (11), une soupape d'air (20) pour commander l'écoulement d'air de façonnage de forme jusqu'à l'agencement de buse (11), une soupape de fluide (35) pour commander l'écoulement de fluide jusqu'à l'agencement de buse (11), et un moyen d'injection de catalyseur réagissant à l'ouverture de la soupape d'air (20) pour injecter un catalyseur dans le flux

d'air de façonnage de pulvérisation dans le pistolet pulvérisateur (10), le moyen d'injection de catalyseur comprenant une soupape de catalyseur à actionnement pneumatique (27), la soupape de catalyseur (27) comportant un orifice d'entrée relié à un tuyau de catalyseur pressurisé (23), un orifice de sortie relié à un passage d'air de façonnage de forme (38) dans le pistolet pulvérisateur et une arrivée d'air de commande (37) reliée pour recevoir de l'air pressurisé de la soupape d'air (20) lorsque la soupape d'air (20) est ouverte, la soupape de catalyseur (27) s'ouvrant en réponse à l'air pressurisé à l'arrivée d'air de commande (37), **caractérisé par** un moyen pour ouvrir la soupape d'air (20) avant d'ouvrir la soupape de fluide (35) lorsque le pistolet pulvérisateur (10) est mis en service et pour fermer la soupape de fluide (35) avant la soupape d'air (20) lorsque le pistolet pulvérisateur (10) est mis hors service et par la soupape de catalyseur étant montée sur le pistolet pulvérisateur (10).

2. Pistolet pulvérisateur à mélange externe de deux composants selon la revendication 1, dans lequel le moyen pour ouvrir la soupape d'air (20) avant d'ouvrir la soupape de fluide (35) lorsque le pistolet pulvérisateur (10) est mis en service et pour fermer la soupape de fluide (35) avant la soupape d'air lorsque le pistolet pulvérisateur (10) est mis hors service comprend une gâchette de déclenchement (28) configurée pour provoquer une ouverture et une fermeture séquentielles de la soupape d'air (20) et de la soupape de fluide (35).
3. Pistolet pulvérisateur à mélange externe de deux composants selon la revendication 1 ou 2, **caractérisé en ce que** la soupape de catalyseur (27) est montée sur le pistolet pulvérisateur (10) adjacente à l'agencement de buse (11).
4. Pistolet pulvérisateur à mélange externe de deux composants (10) selon la revendication 3, et comprenant également un moyen formant orifice pour limiter l'écoulement de catalyseur jusqu'à l'agencement de buse (11) lorsque la soupape de catalyseur (27) est ouverte.
5. Pistolet pulvérisateur à mélange externe de deux composants (10) selon la revendication 3, **caractérisé en ce que** le pistolet pulvérisateur est un pistolet pulvérisateur à main (10) avec l'agencement de buse (11) fixé à une extrémité d'un corps (12), le corps comprenant une poignée (13) comportant une extrémité libre, un moyen pour fixer un tuyau d'air (22) à l'extrémité de la poignée, un manifold (21) fixé à ladite extrémité de poignée, le manifold (21) comportant un premier passage et un deuxième passage, un moyen fixant un tuyau de fluide au manifold (21) pour connexion au premier passage,

- un moyen fixant un tuyau de catalyseur (23) au manifold pour connexion au deuxième passage, un deuxième tuyau de fluide relié entre le premier passage de manifold et le corps adjacent à l'agencement de buse, et un deuxième tuyau de catalyseur (26) relié entre le deuxième passage de manifold et l'orifice d'entrée de soupape de catalyseur. 5
6. Pistolet pulvérisateur à mélange externe de deux composants selon la revendication 5, **caractérisé en ce que** le moyen formant orifice est situé dans le deuxième tuyau de catalyseur (26) pour limiter l'écoulement de catalyseur jusqu'à l'agencement de buse (11) lorsque la soupape de catalyseur (27) est ouverte. 10 15
7. Pistolet pulvérisateur à mélange externe de deux composants selon la revendication 6, **caractérisé en ce que** des moyens sont prévus pour fixer le deuxième tuyau de fluide (22) et le deuxième tuyau de catalyseur (26) l'un à l'autre. 20
8. Pistolet pulvérisateur à mélange externe de deux composants selon la revendication 1, **caractérisé en ce que** la soupape d'air commande l'écoulement d'air de façonnage de forme et d'air d'atomisation. 25
9. Pistolet pulvérisateur pour atomiser un fluide et mettre en contact le fluide atomisé avec un catalyseur à un emplacement à l'extérieur du pistolet pulvérisateur (10), le pistolet pulvérisateur comprenant un corps (12), un agencement de buse (11) fixé au corps (12), une soupape d'air adaptée à commander l'écoulement d'air de façonnage de forme jusqu'à l'agencement de buse (11), une soupape de fluide adaptée à commander l'écoulement de fluide jusqu'à l'agencement de buse (11), une soupape de catalyseur à actionnement pneumatique, normalement fermée (27) comportant un orifice d'entrée de catalyseur pressurisé et un orifice de sortie relié à un passage d'air de façonnage de forme (38) dans le pistolet pulvérisateur (10), la soupape de catalyseur (27) s'ouvrant pour injecter un catalyseur dans un écoulement d'air de façonnage de forme dans le passage d'air (38) en réponse à une augmentation de la pression d'air en aval de la soupape d'air (20) lorsque la soupape d'air (20) est ouverte, **caractérisé par** une soupape d'air adaptée à commander l'écoulement d'air d'atomisation jusqu'à l'agencement de buse (11), un moyen formant gâchette de déclenchement pour ouvrir la soupape d'air (20) avant d'ouvrir la soupape de fluide (35) lorsque le pistolet pulvérisateur (10) est mis en service et pour fermer la soupape de fluide (35) avant la soupape d'air (20) lorsque le pistolet pulvérisateur est mis hors service, et par la soupape de catalyseur (27) étant montée sur le pistolet pulvérisateur. 30 35 40 45 50 55

10. Procédé pour pulvériser une matière comportant un premier composant et un deuxième composant, **caractérisé en ce qu'il** comprend les phases consistant à :

- a) faire passer un écoulement d'air pressurisé jusqu'à un agencement de buse (11), au moins une partie dudit écoulement d'air façonnant la forme de la première matière atomisée ;
- b) ouvrir une soupape de deuxième matière en réponse à l'écoulement d'air pressurisé jusqu'à l'agencement de buse (11) pour injecter une deuxième matière dans l'écoulement d'air de façonnage de forme ;
- c) ouvrir une soupape de première matière une fois que l'écoulement d'air de façonnage de forme pressurisé passe pour distribuer une première matière jusqu'à l'agencement de buse (11) pour atomisation ; et
- d) mettre en contact la première matière atomisée avec l'écoulement d'air de façonnage de forme et la deuxième matière.






FIG. 1







FIG. 2




**FIG. 3**



**FIG. 4**



**FIG. 5**



**FIG. 6**